【国際公開パンフレット】

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication I 4 July 2002 (04.07.2002)

PCT

WO 02/051452 A1

(51)	International Patent Classification?:	
	B65B 55/02	

(25) Filing Language:

(30) Priority Data: 00128318.3 22 December 2000 (22.12.2000) 1EP

(71) Applicant (for all designated States except A7; US): NO-VARTIS AG [CH/CH]: Lichtstrasse 35, CH-4056 Basel

(71) Applicant (for A? only): NOVARTIS-ERFINDUNG VERWALTUNGSGESELLSCHAFT M.B.H. [AT/AT]; ... Brunner Strause 59, A-1230 Vienna (AT).

(72) Investors; and
(75) Investors/Applicants (for US only): FETZ, Andrea
(CIVCII): Ringstrasse 9, CII-8620 Westzikon (CII), KIS,
Gyfrgy, Lajos (CII/CII): Keberlüstrasse 21, CII-8273 Tribolhingen (CH), PEFIOT, Michel [FR/R]; Louissement
Heasuregard N* 13, I-477100 Annonney (I/R).

A61L 2/20. (74) Agest: BECKER, Konrad; Novariis AG, Corporate Intellectual Property, Patent & Trademark Department, CII-4002 Basel (CII).

(84) Designated States (regional): Eurasian potent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DIA, DK, ES, FI, FR, GH, GR, HE, FT, LU, MC, NI., PT, SE, TR).

usueds: with international search report before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guid-ance Notes on Codes and Abbreviations" appearing at the begin-ning of each regular issue of the PCT Gazette.

C (54) TUM: PROCESS TO IMPROVE STABILITY OF A PHARMACHUTICAL COMPOSITION

PCT/EP01/15126

PROCESS TO IMPROVE STABILITY OF A PHARMACEUTICAL COMPOSITION

The present invention describes in particular a method to improve the stability of a pharmaceutical composition by contacting said composition with a polymeric material comprising in particular an ethylene oxide sterilization step.

Pharmaccutical compositions, in particular aqueous pharmaccutical compositions are typically provided in containers, which containers must be sterilized before filling. A problem arises if a container comprises a squeezable material such as polyethylene (PE), polypropylene (PP) and / or polyethylene terephthalate (PET) because these materials may for example not be treated with heat, because these may melt. Alternative sterilization treatments are known in the prior art and is for example ethylene oxide (ETO) treatment or gamma irradiation treatment.

We have found that the stability of an aqueous pharmaceutical composition is typically unacceptable if filled into PE containers which have been previously sterilized by gamma irradiation treatment as known and practiced in the prior art.

Further we have found that the problem may be solved if the sterilization of an empty PE, PP and/or PET container is carried out with ETO e.g. as known and practiced in the prior art before filling said empty container with an aqueous pharmaceutical composition.

The present invention therefore relates in particular to the use of an ETO sterilized PE, PP and/or PET container to improve the stability of an aqueous pharmaceutical composition, in particular to improve the stability of a composition being susceptible to oxidative degradation.

As used herein, ETO sterilized, refers in particular to the treatment steps of:
Exposing a container, in particular an empty PE, PP and/or PET container, to ethylene odde
(ETO) at room temperature, at a concentration and for a time sufficient to achieve sterility;
and thereupon, removing said ETO under aseptic conditions from said container for a period
sufficient to achieve an ETO content of less than 1 ppm.

Therefore, an ETO sterlized container is typically a container, which has been subjected to said treatment steps.

PCT/EP01/15126

-2-

The following parameters are preferably applicable for sald ETO sterilization procedure: The ETO concentration is typically characterized by its composition, namely it contains for example 25% (vol. / vol. at room temperature) nitrogen, more preferably 50% and in particular 75% nitrogen and/or carbon dioxide.

The ETO exposure time sufficient to achieve sterility is generally carried out for a time of 0.5 – 24 hrs, preferably 2 – 15 hrs and more preferably for a period of 3 – 12 hrs.

The ETO removal time, for a period sufficient to achieve an ETO content of less than 1 ppm, is typically for a period of 1 – 20 days, preferably 5 – 15 days, and more preferably for 8 – 10 days.

Removing of said ETO is typically carried out by air diffusion and/or by flushing said container aseptically with a gas selected from nitrogen, argon, carbon dioxide, air and preferably with nitrogen.

The present invention further relates to a method to improve the stability of a pharmaceutical composition which is sensitive towards addation, comprising the steps of:

- exposing a squeezable container, in particular an empty PE, PP and/or PET container, to ethylene oxide (ETO) at room temperature, at a concentration and for a time sufficient to achieve sterility,
- removing said ETO under aseptic conditions from said container for a period sufficient to achieve an ETO content of less than 1 ppm,
- transferring under a septic conditions a pharmaceutical composition into said sterilized container, and
- dosing said container comprising said pharmaceutical composition with a closing device.

The above method steps are typically carried out in a conventional manner or in an analogous manner to that described in the examples or in a manner as described in the examples.

In the context with the present invention the preferred embodiments are described above and below.

As used herein, stabilization relates to the stability of the pharmaceutical composition in total and in particular to the stability of the active ingredient itself when exposed to storage (shelf life stability).

rizabene.

PCT/EP01/15126

- 3 -

The term squeezable material relates preferably to a plastic material and in particular to low density polyethylene (LDPE), high density PE (HDPE), polypropylene (PP), (PET) and mbxtures thereof. A preferred material is LDPE and HDPE, even more preferred is LDPE.

The term container relates preferably to a bottle, in particular to a bottle as used for providing liquid aqueous pharmaceutical compositions. A highly preferred container is a bottle comprising LDPE.

Consequently, the term container relates in particular to a polyethylene bottle and in particular to a LDPE bottle. Such bottles may optionally contain further auxiliarics such as a light absorbing material e.g. titanium dioxide, a color pigment, a UV-absorber, an antioxidant and/or the like.

As used herein, the LDPE material typically contains no antioxidant, however HDPE may contain an antioxidant such as e.g. butylhydroxytoluene (BHT). In an example, a bottle is manufactured from LDPE containing no antioxidant, its cap from HDPE containing BHT.

A pharmaceutical active compound is e.g. selected from the group of compounds which act for example as:

Anti-inflammatory drugs, such as steroids, e.g. dexamethasone, fluorometholone , hydrocortisone, prednisolone; or so-called non-steroidal anti-inflammatory drugs (NSAID) such as COX-inhibitors, e.g. diclofenac, ketorolac, or Indomethacin; Antiallergic drugs, selected e.g. from cromolyn, ketotifen, levocabastine, olopatadine, and

Drugs to treat glaucoma (in particular intraocular pressure treatment), selected e.g. from latanoprost, 15-keto-latanoprost, unoprostone isopropyl, betaxolol, clonidine, levobunolol and timolol:

Anti-Infective drugs, e.g. selected from chloramphenicol, chlorietracycline, gentamycin, neomycin, ofloxacin, polymyxin B and tobramycin;

Antifungal drugs, e.g. selected from amphotericin B, fluconazole and natamycin; Anti-viral drugs such as acyclovir, formivirsen, garciclovir, and trifluridine; Anesthetic drugs, e.g. selected from cocaine hydrochloride, lidocaine and tetracaine hydrochloride;

Miotics, e.g. selected from carbachol, pilocarpine and physostigmine;

PCT/EP01/15126

.

Carbonic anhydrase inhibitors, e.g. selected from acetazolamide and dorzolamide;
Alpha blocking agents, e.g. selected from apracionidine and brimonidine; and
Antioxidants and/or vitamins, e.g. selected from retinol, retinol acetate, and retinol palmitate.

Preferred pharmaceutically active compounds are selected from the group of antiinflammatory drugs, antiallergic drugs and drugs to treat glaucoma.

Other preferred pharmaceutically active compounds are selected from the group of dictofenac, 15-keto-latanoprost, ketorolac, ketotifen, latanoprost, levobunolot, levocabastine, ofloxacin, pilocarpine, polymyxin B, prednisolone, retinol acid, retinol acetate, retinol palmitate, tetracycline, unoprostone isopropyl, and pharmaceutically acceptable salts thereof.

More preferred pharmaceutically active compounds are selected from the group of, betaxolol, chloramphenicol, dictofenac, ketotifen, levobunciol, levocabastine, pilocarpine, retinole acid, retinol, retinole acetate, retinol palmitate, unoprostone isopropyl, and pharmaceutically acceptable salts thereof.

Highly preferred is ketotifen, retinole acid, retinol, retinol acetate, retinol palmitate, unoprostone isopropyl, and pharmaceutically acceptable salts thereof.

Very particular preferred is ketotifien and pharmaceutically acceptable salts thereof,e.g. the hydrogen furnarate (hereinafter this salt is often referred to as Compound A).

As used herein, a pharmaceutical composition is characterized by the carrier wherein said pharmaceutical active compound is mixed, suspended, dissolved and/or partially dissolved. Such a carrier may be chosen e.g. from a wide variety of carriers used preferably for ophthalmic compositions. It may be based on a solvent selected from the group consisting of water, mbutures of water and water-miscible solvents, such as C₁- to C₇-alkanols, e.g in the case of compound A glycerol. A highly preferred carrier is water. The concentration of the carrier is, typically, from 1 to 100000 times the concentration of the active ingredient. The term aqueous typically denotes an aqueous composition wherein the carrier is to an extent of >50%, more preferably >75% and in particular >90% by weight water.

PCT/EP01/15126

٠5٠

A preferred pharmaceutical composition is preferably adapted to ophthalmic prerequisites (e.g. ocular compatibility) and is in particular an ophthalmic composition.

For Compound A typical concentrations are:

- i) 0.025%
- B) 0.05%

Further preference is given to a pharmaceutical composition which is suitable for ocular administration. Therefore such a pharmaceutical composition preferably comprises further ingredients in order to meet the prerequisites for ocular tolerability.

In a particular aspect, the present invention relates to the stabilization of an ophthalmic composition and in particular to an aqueous ophthalmic composition.

Further aspects of the present invention are those disclosed in all dependent and independent claims.

A further aspect of the present invention is the use of a LDPE bottle, which has been subjected to ETO exposure e.g. in accordance to the working examples of the present application, for improving the stability in particular towards coddation of an ophthalmic composition, e.g. a ketotifen 0.025% solution, which composition is subsequently transferred into said bottle in accordance to the disclosure of the present invention.

As used herein % refers to weight / weight (W/W) if not specified differently.

The pharmaceutical compositions of the present invention may be used for the known indications of the pharmacologically active agent.

In a further aspect the present invention provides a container containing a sterile pharmaceutical composition, which container has been ETO sterilized and is obtainable by a method or process as described above,

- a) wherein the active is other than ketotifen
- b) contains ketotifen and is produced other than a process as described in an example.

PCT/EP01/15126

-6-

In yet a further aspect the present invention provides an unclosed ETO sterilized container containing a sterile pharmaceutical composition.

In yet another aspect the present invention provides an unclosed container treated by ETO as described herein containing a sterile pharmaceutical composition, in particular a ketotilen composition.

The closing device of an above described container may be manufactured from PE, PP and / or PET, such as HDPE, and might still be stertilized by gamma irradiation, in particular it said closing device will – to a substantial degree – not contact an above pharmaceutical composition.

Example 1

Ophthalmic eye drop composition comprising ketotifen.

The manufacture of the ophthalmic solution is described for a typical example, All the ingredients are dissolved in water for injections and the pH of the solution is adjusted. The solution is then brought to the final weight and sterile-filtered into a bulk container which is then used to fill the product into sterilized containers. Manufacture is carried out according to GMP guidelines.

The solution is filled into pre-sterilized bottles and plugged and capped with sterile components within a sterile environment using aseptic techniques.

Development studies showed that steam sterilization (i.e. terminal sterilization) was not acceptable due to heat-sensitivity of product and container (PE-bottle). Sterilization by filtration with subsequent aseptic filling into sterile containers is standard industry practice for ophthalmic solutions.

The bulk solution is routinely assessed for bioburden prior to sterile filtration and the EU limit of 10 organisms per 100 ml is adhered to. The sterilizing grade membrane filters are tested for integrity and checks on pH, osmolality, odor and physical appearance provide suitable inprocess controls.

PCT/EP01/15126

-7-

A ketotifen eye drop solution comprises e.g.:

Composition	
ketotilen hydrogen tumarate	0.0345%
(ketotifen content)	(0.025%)
glycerol, pure compound	2.125%
benzalkonium chlorida	0.01%
sodium hydroxide 1N	0.074%
water for injection ad	100 ml
pH	5.32
Osmolality (mOsmol)	240

Example 2

The stability of the example 1 composition is investigated for their shelf stability in containers (or packaging components) being sterilized with different methods of sterilization.

The packaging components of Ketotifen 0.025 % Eye Drops are sterilized by gamma irradiation with a minimum dosage of 25 kGy (sample III). Six batches of 10 to 400 litres are made for stability testing.

The release results from these batches are satisfactory with no significant variation between batches. However, the results of stability tests show significant differences. While some batches remain stable for a longer time, others show a significant decrease of the active compound ketotiten fumarate already within months. It is presently assumed that this phenomenon may be related to the gamma irradiation of the bottles. Therefore, an accelerated stability study is carried out to test this hypothesis. Ketotifen 0.025% Eye Drop solution is filled into untreated bottles, gamma irradiated bottles and bottles sterilized by ethylene oxide and all the samples are stored at 80°C for 15 hours. The test results are compared in the table reproduced infra:

Based on these data, it is observed that sterilization of the LDPE bottles and droppers by ethylene codde is a superior treatment for Ketotifen 0.025%. Eye Drops. It should be emphasized that the containers will only be used when residual ethylene codde has fallen below the 1ppm level (e.g. ventilation of the containers for about two weeks after ETO exposure (treatment)). The HDPE closures might still be sterilized by gamma irradiation since they are not in contact with the eye drops.

PCT/EP01/15126

- R -

Sample	1	10	iii	IV	V
0-value;				<u> </u>	
pH	5.28	5.28	5.25	5.40	5.42
Osmolality (mOsmol)	238	238	240	241	244
% ketotilen	100.2	100.2	89.8	99.8	102.4
% degradation product (n.d.	n.d.	·· n.t.	n.d.	nd
% degradation product II	n.d.	n.d.	0.05	n.d.	n.d.
stress test at 80°C, 15	+		 		
hours:	i			1	
pH	5.2	4.83	4.75	5.22	5.24
Osmolality (mOsmol)	241	244	241	241	248
% ketotilen	98.8	91.6	88.6	94.5	97.7
% degradation product l	~0.05	~1.4	1.2	n.d.	n.d.
% degradation product if	-0.1	-3.2	2.6	n.d.	n.d.
	I	l	ŀ	1	

Legend:

Sample I: Freshly prepared eye drops filled in untreated PE bottles.

Sample II: Freshly prepared eye drops filled in gamma irradiated (40 kGy) PE bottles.

Sample III: Freshly prepared oye drops being subsequently stored at 5°C for several days, filled in gamma irradiated (at least 25 kGy) PE bottles.

Sample IV: Freshly prepared eye drops aseptically filled in ETO sterilized PE bottles.

Sample V: Repetition of IV.

Degradation product I and II respectively denote ketotifen N-oxide which is an oxidation product of ketotifen. It exists in form of two diastereomers with the same stoichiometric formula.

% denotes total weight %

n.d. means:

not detectable; below limit of detection

n.t. means: not determinable; above limit of detection, but below limit of quantitation

The HPLC method has been shown to be selective for ketotilen hydrogen furnarate as well as to all the following known impurities which might possibly be found in the eye drops as follows:

PCT/EP01/15126

Shelf life stability:

The finished product, ketotifen 0.025 % eye drops stored in ETO sterifized PE containers, exhibit an improved stability compared with that of ketotifen 0.025 % eye drops stored in gamma irradiated PE containers (sample III). The results demonstrate the good stability of ketotifen 0.025 % eye drops for 12 months when stored at temperatures up to 25 °C.

Conclusion:

Sterilization of the containers by ethylene oxide is the method of choice since gamma irradiation was shown to be detrimental to the stability of the solution.

PCT/EP01/15126

- 10 -

Claims

- Method to Improve the stability of a pharmaceutical composition which is sensitive towards oxidation, comprising the steps of:
- exposing an empty PE, PP and/or PET container to ethylene oxide (ETO) at room temperature, at a concentration and for a time sufficient to achieve sterility,
- removing said ETO from said container under aseptic conditions for a period sufficient to achieve an ETO content of less than 1 ppm,
- transferring under aseptic conditions a pharmaceutical composition into said sterilized container, and
- closing said container comprising said pharmaceutical composition with a closing device.
- 2. Method of claim 1, wherein said pharmaceutical composition is an aqueous ophthalmic composition.
- Method of claim 1, wherein said container is a LDPE and/or HDPE container, more preferably a LDPE container, and in particular a LDPE container.
- 4. Method of claim 1, wherein said pharmaceutical composition comprises a pharmaceutically active ingredient selected from the group consisting of dictofenac, 15-keto-latanoprost, ketorolac, ketorilac, ketorilac, ketorolac, ketorilac, ketorolac, ketorol
- 5. Method of claim 1, wherein said ETO is removed air diffusion and/or by flushing said container aseptically with a gas selected from nitrogen, argon, carbon dioxide, air and preferably with nitrogen.
- 6. Method of claim 1 or 6, wherein said ETO is removed for a period of 1 20 days, preferably 5 15 days, and more preferably for 8 10 days.
- 7. Method of claim 1, wherein said container is exposed to ETO for a period of 0.5-24 hrs, preferably 2-15 hrs and more preferably for a period of 3-12 hrs.

PCT/EP01/15126

- 11 -

- 8. Method of claim 1, wherein said ETO contains 25% (vol. / vol. at room temperature) nitrogen, more proferably 50% and in particular 75% nitrogen and/or carbon clioxide.
- 9. Method of claim 1, wherein the closing device is sterilized via gamma irradiation.
- 10. A process for the production of a stable pharmaceutical composition in a container, comprising the steps of:
- a) sterilizing a container, in particular a PE and/or PP container, with ethylene code (ETO) at room temperature, at a concentration and for a time sufficient to achieve sterility,
- b) removing said ETO from said container under aseptic conditions for a period sufficient to
- achieve an ETO content of less than 1 ppm, for example under air diffusion conditions, c) transferring under aseptic conditions a pharmaceutical composition into said sterilized container, and
- d) closing said container comprising said pharmaceutical composition with a closing device.
- 11. A process of claim 10, wherein said closing device is sterilized via gamma irradiation.
- 12. Use of an ETO (ethylene oxide) sterilized PE, PP and/or PET container to improve the stability of an aqueous pharmaceutical composition, in particular to improve the stability of a composition being susceptible to oxidative degradation.

【国際調査報告】

		_		
	######################################	_	Internation Appl	leation No
	INTERNATIONAL SEARCH REPOR	Τ	PCT/EP 01/	/15126
	TO A DOCUMENT OF THE PARTY OF T			
IPC 7	A61L2/20 B65B55/02			1
				!
According to	intersettunal Passed Classification (IPC) or to both estional classificat	ion and IPC		
B. FELDS	STARCHED			
Mirimum de	currentation sourcesco (classification system tolkowed by classification	symbols)		
IPC 7	A61F A61J B65B A61L			1
1				
Degmeste	ton searched other then minimum opportunition to the extent that to	ch decuments are inch	and in the Seids on	erched
1				
Electronic d	mia base consulted during the International exect (name of data base	and, where precioel	scorch terms used) -
EP0-1n	ternal, WPI Data			•
ĺ				
Į.				
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT			
Category *	Citation of document, with indication, whose appropriate, of the son	vert passagns		Relevent to date No.
lx ·	WO CO 73156 A (NOVARTIS ERFIND VE	RMALT		.1-4,9-12
l"	EMBH ;KIS GYCERGY LAJOS (CH); KRA			
Ī	EC) 7 December 2000 (2000-12-07)			
	page 1, paragraph 4 -page 2, line	2.	,	
Y				5-8
i	· · · · · · · · · · · · · · · · · · ·			
Y	US 6 132 679 A (CONVISER STEPHEN	A)		5-7
1	17 October 2000 (2000-10-17)			
l.	column 1, line 34 -column 2, line	4		1 10
A	column 6, line 38-58			1,10
	figure 1			
				*
l۷	EP 1 040 840 A (ETHICON INC)			8 1
i i	4 October 2000 (2000-10-04) column 3, line 19-42 column 3, line 53-56			
1	column 3, line 19-42			1
A	column 3, line 53-56			1,5-7,10
1	column 4, line 15 -column 6, line	24		
1	- -	,		
L		/		
X Feet	her documents are listed in the continuation of tex C.	Patent temby	members are Rated	in anoros.
		<u> </u>		
* Apodei co	negorise of checi documents:	T inter document put or paority case an	bated after the Into	mational filing date
"A" docum	ant datining the general while of the art which is not issed to be of particular solications	or profity case and check to endermise	d not in coeffict with d the principle or th	the application but
T min	imed to be of particular editority to a father action of the supermittered on or given the later matter and the supermittered on the supermittered of the su	Invention M. Assessant of section		dament browners
(Chart		cannot be conside	red novel or central	teimed invention to considered to current to telescaping
f. quanti	nd which may throw doubts on pricely chain(s) or is cled to establish the publication date of another n or other special reason (so epecifics)	CODWII ES EMOVIE Citrar la lancación "Y	e mai seperatura de qui Se mai servica de qui	CLETTON & WHICH SENS CHITCHES REPORTED IN
777	n or Other special reason (as epacified) ant referring to arr and disclosure, use, coffibilion or	document is come	red to involve an in	delined leveration scordive step when the one other such docu-
- other	7023	ments, such cons	imation being abyto	no to a penson elded
The document	est published prior so the interestioned. Uling date but hen the priority date claimed.	f, quantum wateron		
	entata) completion of the international search		The International Co.	
1	·			
1 2	4 May 2002	05/06/2	002	
Name and	meding extreme of the ISA Exercises Patent Office, P.B. 5818 Potostosio 2	Astronzed officer		
I	M 2200 M. Plants. Tel. (+31-70) 340-2040, Tx. 31 051 epo nl.	_		
ł	Tet. (+31-70) 340-2040, Tx. 31 001 epo is, Fex: (+31-70) 340-3016 ·	Rosenbl	att, T	

	INTERNATIONAL SEARCH REPORT	PCT/EP 01	/15126
C-(Continu	MIGH) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Okation of cocument, with instruction, where appropriate, of the relevant passages		Palayant to centra No.
X	GB 780 483 A (HOECHST AG) 7 August 1957 (1957-08-07) page 1, line 63 -page 2, line 95		1,10,12
x	CH 483 963 A (U M P VENESTA LTD) 15 January 1970 (1970-01-15) column 3, line 13-42		1,2,10, 12
x	US 5 620 425 A (WELSHER ALLEN ET AL) 15 April 1997 (1997-04-15) column 4, line 9 -column 7, line 11; claims ,101,11	•	1,3,10, 12
X	US 4 482 585 A (OHODAIRA TAKED ET AL) 13 November 1984 (1984-11-13) column 5, line 3-23		1,10,12
A	WO OD 62824 A (STRYKER TECHNOLOGIES CORP) 26 October 2000 (2000-10-26) page 5, line 4 -page 6, line 14		1,5-7,10
ł			
1	· ·	•	
	•		
•			
•			· ·
-	·] '
l			
	·		
Ì			1
		•	l i
			2020
l	•		
			· .
	,		
l			1

cited in energy report		Publication		Petron territy		Publication
100 0076156		date		member(s)		Class
WO 0073156	A	07-12-2000	AU	4758800	A .	18-12-2000
			BR	0011009		19-02-200
			₩O	0073156		07-12-200
			EΡ	1181197	7 A1	27-02-200
			NO	20015706		22-11-200
			ŲS	2002020713	3 A1	21-02-200
US 6132679	A	17-10-2000	AU	1916299) A ·	19-07-1999
			CA	2317532		08-07-1999
			EP	1042010		11-10-2000
			HU	0100076		28-05-2001
			JP	2001526940		25-12-2001
			PL	344750		1911-2001
			WO	9933494	A2	-08-07-1999
EP 1040840	Α	04-10-2000	EP	1040840		04-10-2000
			JP	2000237289	A	05-09-2000
GB 780483	. A	07-08-1957	BÉ	523577	' A	
			FR	67888	E	25-03-1958
			FR	1085194	Α	28-01-1955
CH 483963	A	1501-1970	NONE			
US 5620425	A	15-04-1997	AT	175381	T	15-01-1999
			AU	678610		05-06-1997
			AU .	7821594		23-05-1995
			CA	2151482	A1	11-05-1995
			CN	1115973	А,В	31-01-1996
			DE	69415793		18-02-1999
			DE	69415793		02-09-1999
			DK	680401		30-08-1999
			EP	0580401		08-11-1995
			EP. ES	0862979		09-09-1998
			- MO	2126784		01-04-1999
			IL	9512482 111399		11-05-1995
			JP	8505334		30-10-1998
			ZA	9408179		11-06-1996 08-08-1995
	A	13-11-1984	NONE		-	
JS 4482585						
US 4482585 NO 0062824	Α	26-10-2000	us	6231810	B1	15-05-2001
	A	26-10-2000	ALI	6231810 4471800		15-05-2001 02-11-2000
	A	26-10-2000			A	

フロントページの続き

(51) Int. Cl. 7

FΙ

テーマコード (参考)

B 6 5 B 55/04

B 6 5 B 55/04

Α

B65B 55/10

B 6 5 B 55/10

С

(72)発明者 ギュエルギー・ラヨス・キス

スイス、ツェーハー-8273トリボルティンゲン、ケバーリシュトラーセ21番

(72)発明者 ミシェル・ペピオ

フランス、エフー07100アノネイ、ロティスマン・ボールガール・ニュメロ13番

Fターム(参考) 4C058 AA25 BB07 CC03 DD05 DD07 JJ15 KK03

4C076 AA12 BB24 CC10 GG43

4C086 AA01 AA02 BC21 GA04 GA07 MA17 MA58 ZA33